# **ULTRA-SONIC CUTTER**

# **SONIC-CUTTER**

- Oscillation Frequency: 39.5KHz, Max. Output Power: 30W
- Intricate and accurate cutting with a light touch.
- This ideal handpiece offers excellent maneuverability and there is no vibration to the hand ensuring an accurate and sharp cutting finish.



### \*Not available in Europe.

# Application Samples

For cutting and deburring of plastics




Efficient for cutting and deburring of composite material of FRP and plastic materials.



For cutting of sheet, cloth, etc.

Delicate and beautiful cutting with a light touch can be made on sheet,





Most suitable for accurate correction work required on PCB.



Beautiful cutting finish is made for cutting out designs and patterns on rubber, POP sheet, paper, etc.

# SONIC-CUTTER Standard Set



# Controller (Ultra-Sonic Cutter)

Model	NE80	
Code No.	9928 (230V)	
Code No.	9927 (120V)	

\*Please check the power source plug type (P.66).

Specifications Model: NE80

Oscillating Frequency: 39.5 KHz Oscillating System: Automatic Oscillation, Automatic Trucking

Max. Output Power: 30W Power Source : AC120/230V, 50-60Hz

Dimensions: W150 x D250 x H120 mm Weight: 2.6 kg

# Standard Accessories

- Ground Wire: 1 pc.
- Handpiece Stand (Including mounting parts): 1 set



- Easy operation by ON/OFF Switch.
- Constant frequency provides steady cutting results.
- The controller automatically adjusts the output power depending on load so there is no need to make minor adjustments on the controller during the working process.

# Hand-Held Type Cutter

#### Standard Type

No.	1496	Model	US-15CB
Titaniur	n Type		
Code No.	1493	Model	US-15CBT

### Specifications

Model: US-15CB (Standard Type) US-15CBT (Titanium Type)

Piezoelectric Transducer: Bolt-Clamped PZT Type Weight (w/cord): Approx. 210 g (Standard Type) Cord Length: 3 m

#### Standard Accessories

- · Allen Wrench (1.5 mm): 2 pcs.
- · Hexagonal Wrench (M5), (R1.5): 1 pc. each
- · Spare Set Screw: 4 pcs.
- Spare Blade: 40 pcs.



- Designed compact and lightweight with an easy hand grip to reduce fatigue, the sonic-cutter allows for long continuous operation.
- More efficient and durable Titanium Type is also available.

# Cutter For Machine Attachment

## Standard Type

1498	Model	US-16CB
n Type		
1494	Model	US-16CBT
	1498 m Type 1494	n Type

#### Specifications Model: US-16CB (Standard Type)

US-16CBT (Titanium Type)

Piezoelectric Transducer: Bolt-Clamped PZT Type Weight (w/cord): Approx. 290 g (Standard Type) Cord Length: 3 m

# Standard Accessories

- Allen Wrench (1.5 mm): 2 pcs.
- . Hexagonal Wrench (M5), (R1.5): 1 pc. each
- Air Hose (ø4 mm x 4 m) 0.2~0.4 MPa
- Spare Blade: 40 pcs.
- · Spare Set Screw: 4 pcs.

- Cutter for machine attachment is available with internal coolant air joint to withstand long continuous operation.
- More efficient and durable Titanium Type is also available.

#### SONIC-CUTTER Spare Parts

Product	Description	Code No.	Model	Specifications
-	Foot Pedal	1440	FC-40	ON/OFF switch only
4mm	Spare Blade			Made by NT Co. BDC-200P 30° Spare blade is available at a shop near you.

P. 59